

**SANYO****Cadnica**

Dimensions of Bare Cell	H	15.0 ±0.3	mm
		0.591 ±0.012	inch
	D	10.0 ±0.2	mm
		0.394 ±0.008	inch
d	5.5	mm	
	0.217	inch	

# Cell Type N-50AAA

## Specifications

Nominal Capacity		50mAh	
Nominal Voltage		1.2V	
Charging Current	Standard	5mA	
	Quick	15mA	
Charging Time	Standard	14 to 16Hrs.	
	Quick	4 to 6Hrs.	
Ambient Temperature	Charge	Standard	0 to 45 °C [32 to 113 °F]
		Quick	10 to 45 °C [50 to 113 °F]
	Discharge		-20 to 60 °C [-4 to 140 °F]
	Storage		-30 to 50 °C [-22 to 122 °F]
Internal Impedance(Av.) (at. 50% discharge)		55mOhms (at 1000Hz)	
Weight		4g/0.14oz	
Dimensions(D)x(H) (with tube)		10.5 <sup>0</sup> <sub>-0.5</sub> x 16 <sup>0</sup> <sub>-1</sub> mm	0.41 <sup>0</sup> <sub>-0.02</sub> x 0.63 <sup>0</sup> <sub>-0.04</sub> inch